



REV.	Q'TY	ECN. NO.	APR.	DATE
A				

NOTES:

MATERIALS

- HOUSING:
HI-TEMP.PLASTIC UL 94V-0 BLACK
- CONTACT
COPPER ALLOY,T=0.15mm
GOLD PLATED ON CONTACT AREA
GOLD FLASH PLATED ON SOLDER TAILS UNDER NICKEL PLATED
- SHELL:
BRASS T=0.25
MATTE TIN PLATING OVERALL UNDER NICKEL PLATED

SPECIFICATIONS

- VOLTAGE RATING:30V AC
- CURRENT RATING:WHEN APPLYING CURRENT ONLY TO SIGNAL TERMINALS:
1.0A(FOR TERMINAL NO.2,3 AND 4)
WHEN APPLYING CURRENT ONLY TO POWER TERMINALS:
1.8A(FOR TERMINAL NO.1 AND 5)
0.5A(FOR TERMINAL NO.2,3 AND 4)
- INSULATION RESISTANCE:100M MINIAT 100V DC
- DIELECTRIC WITHSTANDING VOLTAGE:100V(r.m.s)AC FOR 1 MINUTE
- CONTACT RESISTANCE:30m MAX.
- OPERATING TEMPERATURE:-30 TO +80?

DIMENSION IN mm				
TOLERANCE UNLESS OTHERWISE SPECIFIED				
.X±0.35	X°± 5°	APR.	TITLE: MICRO USB 5PIN RECEPTACLE STRADDLE 0.75mm 四脚插,不翻边	
.XX±0.25	.X°± 3°	CHK.	DWG NO.	
.XXX±0.15	.XX°± 1°	DRA. SAMLI 02/08/09	PROJ.	
		SIZE A4	SCALE 5:1	SHEET 1/1 REV. A