



- 备注:
- 1.材料:
 - 1.1 胶芯: LCP+30%G.F UL94V-0
 - 1.2 端子: 磷铜, T=0.12mm; 镍底, 镀金3μ"
 - 1.3 外壳: 不锈钢, T=0.30mm; 表面镀镍100μ"
 - 2.主要特性:
 - 2.1 额定电流: 3A
 - 2.2 接触阻抗: 30mΩ MAX
 - 2.3 绝缘阻抗: 100MΩ MIN 250V DC
 - 2.4 耐压测试: 250V AC
 - 2.5 耐磨性: 温度250±5℃, 时间5±0.5s
 - 2.6 整体插入力: 3.57kgf MAX
 - 2.7 使用寿命: 1.02kgf MIN
 - 2.8 工作温度: -30℃~+80℃

PIN ASSIGNMENT:

Pin No.	Signal Name	Pin No.	Signal Name
A1	GND	B12	GND
A2	TX+	B11	RX-
A3	TX-	B10	RX+
A4	VBUS	B9	PRR
A5	CC1	B8	SMU2
A6	D-	B7	D+
A7	D+	B6	D-
A8	SMU1	B5	VCONN
A9	VBUS	B4	PRR
A10	RX+	B3	TX+
A11	RX-	B2	TX-
A12	GND	B1	GND

Shenzhen City Xiangyunfeiwu
Technology Co., Ltd.

TITLE: USB 3.1Type-C/F 前插后贴板上母座成品

PART NO.: USB-D01

DRAWING NO.:

CHECK:

DRAWN:

REV.: A/0 SIZE: A4 UNIT: M SCALE: 1:1 SHEET: 1/1

