



- Material:**
 - Contacts: Phosphor Bronze
 - Insulator: PBT+30%
 - G. F. UL 94V-0
 - Shell: SPCC
- Mechanical:**
 - Mating: 35N max.
 - Withdrawal Force: 10N min.
 - Durability: 1500 cycles min.
- Electrical:**
 - Current-max (amps) 1.5A
 - Voltage-max (volts) 30V
 - Withstanding Voltage 750V AC
 - Contact Resistance (ohms) 30 milliohms max
 - Insulation Resistance (ohms) 1000 Megohms min.
- Plating:**
 - Contacts: Gold And Tin Over Nickel Plated
 - Shell: Nickel over all plating.
- Environmental:**
 - Temperature Range: -55 to 85

产品图 MANUFACTURE DWG		公差一览表 TOLERANCE UNLESS OTHERWISE		产品名称 USB A/F 双层90度短体卷边			
单位 UNIT	MM		INCH	角法 VIEW	制图 DRAWING	审核 CHKD	张数 1/1
.X	±0.20	.X	±----				
.XX	±0.10	.XX	±----				
.XXX	±0.05	.XXX	±----	比例 SCALE	1:1	设计 DESIGN	核 准 APPD
2013.08.29				版本 AI	图号	CKC1	