



REV	LTR	DESCRIPTION	DATE	APPROVED
A0		依新料号编码原则发行图面	20101106	zhaoci

NOTES:

1. MATERIAL SPECIFICATION:

- 1) HOUSING MATERIAL:SEE PART NO.
- 2) BOTTOM COVER MATERIAL:SEE PART NO.
- 3) SHELL MATERIAL:SEE PART NO.
PLATING:SEE PART NO.
- 4) BACK COVER MATERIAL:SPCC T:0.30mm
PLATING:NICKE.
- 5) TERMINAL: COPPER ALLOY T:0.25mm
PLATING:SEE PART NO.

2. ELECTRICAL CHARACTERISTIC:

- 1) VOLTAGE CURRENT RATING: 1AMP, 30V DC;
- 2) INSULATION RESISTANCE: 1000MΩ MIN;
- 3) CONTACT RESISTANCE: 30mΩ MAX;
- 4) WITHSTANDING VOLTAGE: 500V AC;

3. MECHANICAL:

- 1) MATING FORCE:3.57 KG MAX
- 2) UNMATING FORCE:1.02 KG MIN.

4. 01-3 X XANX X X X X XN●008
1 2 3 4 5 6 7 8

- 1:外壳材质代码: A:黄铜C2680, B:磷铜C5191, C:磷铜C5210, E:双光铁
- 2:外壳电镀代码: A:镀镍12H, B:镀镍24H, C:镀镍48H, D:镀雾镍, E:镀锡, F:镀雾锡
- 3:主体胶芯材质代码: A:PBT, B:LCP, F:PA66
- 4:主体胶芯颜色代码: 1:白色 2:黑色 3:本色 4:蓝色
- 5:后塞材质及颜色代码: A:PBT 白色 B:PBT 黑色 C:PBT 蓝色 D:LCP 本色 E:LCP 黑色 F:LCP 蓝色
- 6:端子材质代码: 1:黄铜C2680, 2:磷铜C5191, A:半金锡15u", B:半金锡30u", C:半金锡15u", D:半金锡30u", E:半金雾锡G/F, F:半金雾锡30u", G:半金雾锡15u", H:半金雾锡30u"
- 7:端子电镀代码: A:半金锡15u", B:半金锡30u", C:半金锡15u", D:半金锡30u", E:半金雾锡G/F, F:半金雾锡30u", G:半金雾锡15u", H:半金雾锡30u"
- 8: 环保代码: N:非环保, R:ROHS, S:SONY, F:ROHS+无卤

Shenzhen City Xiangyunfeiwu
Technology Co., Ltd.

TITLE: USB A F侧插式长体弯脚有后塞

PART NO.: 01●3XXANXXXXXX●008

APPD.: 013●008

CHECK: DRAWN: 赵群 20101106

SIZE: A4 UNITS: M M SCALE: 1 : 1 SHEET: 1 / 1