



RECOMMEND P.C.B Layout (T=1.20mm)
PCB TOLERANCE;±0.05

- NOTES:
 1:MATERIAL:
 <1>SHIELD:BRASS,T=0.2mm
 <2>HOUSING:LCP,G/F FILLED,UL94V-0 RATED
 OR OTHER HIGH PERFORMANCE RESINS.
 COLOR IN BLACK.
 <3>TERMINAL:PHOSPHOR BRONZE,T=0.35mm
 2:CONTACT PLATED:GOLD
 3:PCB TOLERANCES:DIMENSION ±0.05
 4:RETENTION FORCE OF PLUG IN THE JACK IS 10 kgf(min).
 5:SPECIFICATIO:
 DIELECTRIC STRENGTH:AC 500V FOR ONE MINUTE
 INSULATOR RESISTANCE:100M min.AT DC 100V
 CONTACT RESISTANCE:45m max.
 CURRENT RATING:500mA
 OPERATING TEMPERATURE:-30°C ~+85°C

<h1>XYFW</h1>	UNIT :mm	Approved By: JP.Gong	
	.x +/-0.3, .xx +/-0.2 RJ45 沉板式 SMT	Part No:RJ-55A55MMNL	REV. F
Drafted by:JG.CHEN	www.cnxyfw.com		SHEET 1 OF 1