



规格说明: Specifications:

- 1. 额定电流: Current Rating  
1.5A/contact terminal
- 2. 额定电压: Voltage Rating  
30V DC
- 3. 接触阻抗: Contact Resistance  
30 milliohms MAX
- 4. 耐电压: Dielectric Withstanding Voltage:  
500 V AC AT Sea Level
- 5. 绝缘阻抗: Insulation Resistance:  
1000MEGA ohms MIN

物理性能: Mechanical:

- 1. 插拔力: Connector Mate and Unmate Force  
Mate force: 3.57kgf(MAX)  
Unmate force: 1.02kgf(MIN)
- 2. 端子保持力: Terminal Retention  
1.0kgf(MIN)

1. 塑壳: Housing:

Hing Temperature Thermoplastics,

- 2. 端子: Contact: Copper Alloy C2680
- 3. 外壳: Shell: Copper Alloy C2680/SPCC

1. 端子: Contact: Plated Gold in Mating Area;  
Tin On Solder Talls  
端子四周镀50U”(MIN) 锡, 镀金区域镀100—200U” 镀金1U”

铜壳四周镀80U”(MIN) 锡  
Nickel Plating

公差一览表		公差一览表	
TOLERANCE UNLESS OTHERWISE	公差	TOLERANCE UNLESS OTHERWISE	公差
X.±0.15	X.±5°	X.±0.05	X.±2°
XXX±0.02	.XX±1°		

DATE	DATE	UNIT	MM	DRAWING	DWG NO.	NAME	版本	页数
CHECKED	审核	比例	1:1	设计		姓名	VER	SHEET
APPROVE	批准	角注		VIEW				