



规格说明:Specifications:
电气特性:Electrical:

1. 额定电流: Current Rating
1.5A/contact terminal
2. 额定电压: Voltage Rating
30V DC
3. 接触阻抗:Contact Resistance
30 milliohms MAX
4. 耐电压:Dielectnic Withstanding Voitage:
500 V AC AT Sea Level
5. 绝缘阻抗:Insulation Resistance:
1000MEGA ohms MIN

物理性能:Mechanical:

1. 插拔力: Connector Mate and Unmate Force
Mate force:3.57kgf(MAX)
Unmate force:1.02kgf(MIN)
2. 端子保持力: Terminal Retention
1.2kgf(MIN)

原材料:Material:

1. 塑胶:Housing:
Hing Temperature Tnermaplastics,
PBT White/Black
2. 端子>Contact:Copper Alloy C2680
3. 外壳:Shell: Copper Alloy C2680/SPCC

电镀:Finish:

1. 端子>Contact: Plated Gold in Mating Area;
Tin On Solder Talls
2. 外壳:Shell:
Nickel Plating

RBCOMMENDBD P. C. B PATTRN LAY OUT

Shenzhen City Xiangyunfeiwu Technology Co., Ltd.

UNLESS OTHERWISE SPECIFIED TOLERANCE		DRAWN H.Q.huocy		TITLE USB AF 双层直插14.2MM无脚	
.X	±0.20	APPROVED		PART NO. C02	REV. A
.XX	±0.15	DATE 2011.03.18		DOC. NO.	
.XXX	±0.10				
ANG.	±2°				